



## Achiever RT-01 U Low Ground Pressure Tracked Carrier SPECIFICATIONS

**DIMENSIONS / WEIGHT** 

Overall Length 158" (without plow)

170" (extended deck)

194" (extended deck with plow)

Overall Width 89"

Height 91" (without beacon)

Ground Clearance 15"
Weight (no payload) 7,500 lbs
Payload 5,000 lbs

Deck Area 2-Man Cab: 60 x 80"

4-Man Cab: 48" x 80"

<u>PERFORMANCE</u>

Maximum speed 11 miles / hr unloaded

Inside turning radius 0 ft

Climbing ability

uphill 40° (84%)side-hill 15° (27%)

Ground pressure

28" tracks 1.19 PSI (no load)

1.99 PSI (loaded) 33" tracks 1.02 PSI no load 1.62 PSI loaded

Fording / deck height 35" max / 39"

**ENGINE** Deutz AG

Make TCD 3.6 L4, 4 cylinder turbo

Model charged diesel

134 HP at 2,300 RPM 369 ft lbs at 1.600 RPM

Horsepower 369 ft lbs at 1,600

Torque 3.62 liters
Displacement 40 gals
Fuel capacity 2.6 gals.

Achiever RT-01 U Specifications 2023-11-10

DEF tank 4 gals per hour (average)

Fuel consumption Rubber 4-ply belts with

TRACKS 28" D-Dent steel crosslinks

**STEERING** Independent dual joysticks with

cable control for each track

FRAME / SUSPENSION

Type Welded tub
Axle Torsion axle
Tires Solid rubber

Suspension system:

> 2 independent idler wheels with grease hubs

> 8 solid wheels with grease hubs.

2 rear drive sprockets

Dust cap retainers on all road wheels

POWER TRAIN FOR HYDROSTATIC DRIVE

Transmission Hydrostatic, 2-speed

Service Brakes Positive deceleration through the

hydrostatic transmission

Parking brakes Multi-disc, spring applied &

pressure released

**ELECTRICAL** 

Voltage 12v

Batteries 2x 1,060 CCA
Alternator Capacity 120 amps.
Ground Negative

**STANDARD FEATURES** 

1 man open cab

Vinyl seat with slider & 2-point seat belt

Roll over protection structure

Full instrumentation, illuminated panel gauge Fire extinguisher, backup alarm and horn

120v block heater, glow plugs, 12v heated fuel filter,

Secondary fuel filter with water separator Muffler, electric engine shut down system

Oil cooler for hydraulic reservoir

2 High powered LED front & 1 rear light, 1 beacon light

Pg 1 of 5

2" Receiver socket, front and rear

1 Set of operations, parts & service manuals

## Available Options / Features Front Options

Front 2 way hydraulics with 84" straight plow for light brush clearing

16,500 lb electric winch with front wiring & remote control with 12 ft lead

18,000 lb hydraulic winch, fixed front mount with in cab controls



<sup>\*</sup>Specifications subject to change without notice





#### **Achiever RT-01 U Low Ground Pressure Tracked Carrier**

#### **Available Options / Features continued**

**Cab Options** 

Front-mounted brush guard for 1-man cab

Drivers side wire mesh door and side wall (1-man open cab)

Front-mounted brush guard for 2 or 4-man open cab

2-man open cab includes:

2 mechanical suspension vinyl seats with slider & 2-point seat belts

Deck 60" x 80" for 2-man cab

4-man open cab includes:

2 front & 2 rear mechanical suspension vinyl seats with slider & 2-point seat belts

Deck 48" x 80" for 4-man cab

2 front doors (ventilated) for open cab, both sides

2 rear doors (ventilated) for open cab, both sides

Cab mounted front brush guard for 1-man closed cab

1-man closed cab includes:

Front windshield on-off wiper, front windshild washer

Aluminum escape hatch

Sliding left & right side windows

Cab heater/defroster & circulation fan

Door with dual locking system

Front-mounted brush guard for 2 or 4-man closed cab

2-man closed cab includes

2 front mechanical suspension vinyl seats with slider & 2-point seat belts

Front windshield on-off wiper, front windshield washer

Aluminum escape hatch

Sliding left & right side windows

Cab heater/defroster & circulation fan

Deck 60" x 80" for 2-man cab

4-man closed cab includes:

2 front & 2 rear mechanical suspension vinyl seats with slider & 2-point seat belts

Front windshield on-off wiper, front windshield washer

Aluminum escape hatch

Sliding left & right side windows

Cab heater/defroster & circulation fan

Deck 48" x 80" for 4-man cab

Front windshield intermittent wiper (each)

Sun visor

Steering wheel

Driver's 3 point seat belt

Premium cab insulation

Passenger's inside rear view mirror

Additional removable cab entrance step (open or closed cab)

Rear windshield wiper (each)







#### **Achiever RT-01 U Low Ground Pressure Tracked Carrier**

**Cab Options continued** 

Street side rear view mirror

Street side rear view mirror with electric heating

Curb side rear view mirror

Back up camera with heated lens and 7" in-cab waterproof display

DC Comfort Air Conditioning 6,000 BTU/hr, 12v for 1-man cab

Air Conditioning 12,000 Btu/hr, 12v for 2 or 4 man cab

#### **Lighting Options**

Golight Stryker Spotlight on top of cab with guarding & in cab & hand held remote controls

#### **Engine & Cold Weather Options**

Spark arrestor

12v engine coolant heater, 17,200 BTU with 7 day timer

120v hydraulic oil tank heater

120v battery charger

Winter bridge & engine cover for 1-man cab

Synthetic engine oil

Insulated battery box

120v battery heaters

Coolant battery heaters

Glycol coolant

Synthetic hydraulic oil

1,800 watt gas powered portable generator / inverter with on deck storage

#### **Track Options**

Replace 28" D Dent with 33" D-Dent tracks (shipped loose for overseas export)

Replace 28" D Dent with 29" high profile rubber tracks with heat reated aluminum inserts

Replace 28" D Dent with 33" high profile rubber tracks with heat reated aluminum inserts

Ice claws for rubber tracks (12 each side)

#### **Vehicle Options**

Rear 4 way hydraulics with electric connections

Extended deck (12" x 80"W extra)

12" wooden side wall on deck (removable)

24" wooden side wall on deck (removable)

Rear deck ladder

Pintle hook

1st 100 hour maintenance kit (return & supercharge filters)

Additional set of manuals

On site operations and maintenance training


Other options available on request







# Achiever RT-01 U Low Ground Pressure Tracked Carrier Dimensions









# Achiever RT-01 U Low Ground Pressure Tracked Carrier Dimensions

