

UTV International

RT-1200 SG Pioneer Snow Groomer 2 Man Cab

Specifications

<p><u>DIMENSIONS / WEIGHT</u></p> <p>Overall Length 132" Track Width 28" winter track standard</p> <p>Overall Width 84" (with 28" tracks) 100" (with 36" tracks)</p> <p>Overall Height 87" (beacon light adds 5")</p> <p>Ground Clearance 12"</p> <p>Weight & Payload</p> <ul style="list-style-type: none"> - Basic Vehicle 5,950 Lbs. - Load Capacity 2,000 Lbs. 	<p><u>TRACKS</u></p> <p>Type Standard: symmetric 28" winter tracks with rubber belts and steel crosslinks</p> <p><u>WHEELS</u></p> <p>2 drive sprockets 2 20" O.D. solid idler wheels 6 21" O.D. pneumatic tires</p> <p><u>STEERING</u></p> <p>Electro-hydraulic joystick control</p> <p><u>ELECTRICAL</u></p> <p>Voltage 12 V Battery Capacity 850 CCA Alternator Capacity 90 amps Ground Negative</p>
<p><u>PERFORMANCE</u></p> <p>Maximum speed 17 MPH Inside turning radius 0 ft. Climbing Ability</p> <ul style="list-style-type: none"> - Uphill 100% - Side-hill 65% <p>Ground Pressure</p> <ul style="list-style-type: none"> - with 28" tracks 0.95 PSI - with 36" tracks 0.68 PSI 	<p><u>STANDARD FEATURES</u></p> <p>Cab capacity for 2 persons Front & rear receiver sockets Electric engine shut down system Full instrumentation Large windows for all-around visibility Windshield wiper Inside rear-view mirror Sunroof / escape hatch 2-point seat belts for driver & front passenger Heater-defroster 2 Front & 2 rear lights, 1 dome light Beacon light Back-up alarm & horn Deck with payload 2,000 lbs Fire extinguisher 1 Set parts & service manuals</p> <p><u>SNOW GROOMING OPTIONS</u></p> <p>4 way plow 6 way plow 4 way rear hydraulic outlets 6 way rear hydraulic outlets</p> <p><u>AVAILABLE OPTIONS & ACCESSORIES</u></p> <p>Front or rear winch Adjustable seats with high back for driver & front passenger Folding sun visor Circulation fan Sliding rear window 36" winter tracks All season rubber track Foam filled tires Heavy duty solid wheels Custom paint Pintle hook Additional Parts and Service Manuals Other options / features available upon request</p>
<p><u>ENGINE</u></p> <p>Make Fiat Powertrain Technologies Iveco N45MST, 4 cylinder</p> <p>Model 126 HP at 2,200 RPM</p> <p>Horsepower 4.5 liters</p> <p>Displacement 40 gals.</p> <p>Fuel Tank 4 gals per hour</p> <p>Fuel consumption 388 ft lbs at 1,250 RPM (1,900 RPM)</p> <p>Torque</p>	
<p><u>FRAME / SUSPENSION</u></p> <p>Type Welded tub Axels Rubber mounted torsion bars Tires Pneumatic mounted on steel rims</p>	
<p><u>POWER TRAIN FOR HYDROSTATIC DRIVE</u></p> <p>Transmission 2-Speed Hydrostatic Drive Sprockets Rubber on steel hub Parking Brakes Multi-disc, spring applied & pressure release Service Brakes Positive deceleration through the hydrostatic transmission</p>	

Specifications subject to change without notice

